



**JST08X-1000CW 8A TRIAC**

Rev.A.1.1


**DESCRIPTION:**

The JST08X-1000CW triac is suitable for general purpose


Peak pulse voltage ( $T_j=25$ ; non-repetitive, off-state; FIG.7)	$V_{pp}$	4	kV
--	----------	---	----

**ELECTRICAL CHARACTERISTICS ( $T_j=25$ )**

ORDERING INFORMATION



MARKING



# JST08X-

**FIG.1:** Maxim  
on-state curre






FIG.7 Test circuit for inductive and resistive loads to IEC-61000-4-5 standards








Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co., Ltd. assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information. This document supersedes and replaces all information previously supplied.

 is a registered trademark of Jiangsu JieJie Microelectronics Co., Ltd.

Copyright © 2025 Jiangsu JieJie Microelectronics Co., Ltd. All rights reserved.